Smart Sockets™ 36 mm

Part Number: 21363



200 - 2.000 Nm **DATA LOGGING BLUETOOTH CONNECTIVITY RECHARGEABLE BATTERY CONNECTIVITY WITH E-RAD**

SPECIFICATIONS

- TORQUE RANGE: 200 2.000 Nm
- WEIGHT: 1,2 Kg
- SQUARE DRIVE: 1" inch square drive
- **BATTERY:** Built-in rechargeable li-ion battery
- CONNECTIVITY: Bluetooth
- DATALOGGING: Download logs (XLS, CSV, PDF)
- TRACKING: Pass & Fail, Track and Peak
- CERTIFICATION: According to ISO 17025
- **MAXIMUM DEVIATION:** +/- 1%*.
 - * Test results from RAD's certified calibration lab

RAD CONNECT - PRODOCS

- · Tool info
- Stored logs
- Torque graphs
- Process job
- Peak torque
- Export log as .CSV file.



DIMENSIONS IN MM



TOOL KIT INCLUDING

- Smart Socket[™] 36 mm
- Locking pin and o-ring
- Weatherproof storage case
- Calibration certificate
- User manual.



ACCESSOIRES	
Product	Part number
Square drive insert 1" to ¾"	11749
Magnetic Hex Reducer 36 mm -> 32 mm	200886
Magnetic Hex Reducer 36 mm -> 30 mm	200887



Lithium-ion



Impacting





connectivity



Software



Smart SocketsTM 110 mm

Part Number: 331339



1.620 - 16.200 Nm **DATA LOGGING BLUETOOTH CONNECTIVITY RECHARGEABLE BATTERY CONNECTIVITY WITH E-RAD**

SPECIFICATIONS

- TORQUE RANGE: 1.620 16.200 Nm
- WEIGHT: 8,0 Kg
- **SQUARE DRIVE:** 1½" inch square drive
- **BATTERY:** Built-in rechargeable li-ion battery
- CONNECTIVITY: Bluetooth
- DATALOGGING: Download logs (XLS, CSV, PDF)
- TRACKING: Pass & Fail, Track and Peak
- CERTIFICATION: According to ISO 17025
- **MAXIMUM DEVIATION:** +/- 1%*.
 - * Test results from RAD's certified calibration lab

RAD CONNECT - PRODOCS

- · Tool info
- Stored logs
- Torque graphs
- Process job
- Peak torque
- Export log as .CSV file.



DIMENSIONS IN MM



TOOL KIT INCLUDING

- Smart Socket[™] 100 mm
- Locking pin and o-ring
- Weatherproof storage case
- Calibration certificate
- User manual.



ACCESSOIRES	
Product	Part number
Magnetic Hex Reducer 100 mm -> 60 mm	300133
Magnetic Hex Reducer 100 mm -> 80 mm	300134









connectivity



Software

