



**135 - 1.350 Nm**

**DATA LOGGING**

**BLUETOOTH CONNECTIVITY**

**RECHARGEABLE BATTERY**

**CONNECTIVITY WITH E-RAD**

## SPECIFICATIONS

- **TORQUE RANGE:** 135 - 1.350 Nm
- **WEIGHT:** 1,2 Kg
- **SQUARE DRIVE:** 3/4" inch square drive
- **BATTERY:** Built-in rechargeable li-ion battery
- **CONNECTIVITY:** Bluetooth
- **DATALOGGING:** Download logs (XLS, CSV, PDF)
- **TRACKING:** Pass & Fail, Track and Peak
- **CERTIFICATION:** According to ISO 17025
- **MAXIMUM DEVIATION:** +/- 1%\*

\* Test results from RAD's certified calibration lab

## RAD CONNECT - PRODOCS

- Tool info
- Stored logs
- Torque graphs
- Process job
- Peak torque
- Export log as .CSV file.



## DIMENSIONS IN MM



## TOOL KIT INCLUDING

- Smart Socket™ 29 mm
- Locking pin and o-ring
- Weatherproof storage case
- Preinstalled tablet with RAD Connect – PRODOCS App
- Calibration certificate
- User manual.



## ACCESSOIRES

Product	Part number
Various sizes Magnetic Hex Reducers	On request



Safe & Reliable



Lithium-ion battery



According to European standards



Bluetooth connectivity



Software data exchange



Accredited ISO/IEC 17025