

B-RAD[®] XTREME 1500 2000-M

PN: 32653

PN: 32654



Screen Display

Level up your torque power with the all-new B-RAD X 1500/2000-M. Engineered for superior performance in a compact, high-efficiency design, it delivers the precision and control needed for demanding industrial applications while bringing the award-winning B-RAD X Series technology to a lower torque range.

SPECIFICATIONS Imperial (Metric)

Torque Ranges:

150 ft-lb – 1500 ft-lb (200 Nm - 2000 Nm)

Speed: 9.3 RPM

Weight: 13.1 lbs. (6 Kg)


Square Drive: 1"

Noise Level: 75 dBs

Repeatability: $\pm 2\%$

Accuracy: $\pm 3.5\%$ accuracy full scale

DIMENSIONS



Dimension A
in (mm)

10.44 (265)

Dimension B
in (mm)

2.7 (69)

Dimension C
in (mm)

3.62 (92)

Dimension D
in (mm)

13.75 (357)

TOOLKIT

- Cast Reaction Arm (22325)
- (2) 18V batteries
- Charger
- Durable case



Class 1 Division 2
Group A, B, C, D T4




SUITABLE REACTION ARMS

Angled
PN: 14213



Double Ended Arm
PN: 19094



Double Ended Blank
PN: 34759



Blank
PN: 34738



Deep Socket
PN: 17375



Retaining Ring
PN: 17375



radtorque.com